

## CCR 59

TYPE	WEIGHT RANGE	CAPACITY
KK	100 - 700 gr	up to 2500 pcs/h., E-motor 1,1 kW, 1400 rpm, n cone 27 rpm
KM	100 - 700 gr	
KG	200 - 1200 gr	up to 3600 pcs/h., E-motor 1,1 kW, 1400 rpm, n cone 39 rpm
GM	400 - 1600 gr	
GG	400 - 2000 gr	up to 5000 pcs/h., E-motor 1,1 kW, 1400 rpm, n cone 57 rpm

DIMENSIONS		WEIGHT	CONNECTED LOAD
Length	1180 mm	nett 510 kg	230/400 V 3 ph 50 Hz + earth 1,1 KVA, with oiling 4,1 KVA
Width	1180 mm	gross 580 kg	
Height	1760 mm	Shipping volume 2.8 m <sup>3</sup>	

### OPTIONS

#### CCR 59 without oil

- Infeed conveyor
- Discharge conveyor with discharge cone
- Heating with fan
- Frequency inverter for variable cone speed
- Flour duster
- Flour duster with independent drive (only in combination with discharge conveyor)
- Water dripping device
- Final rounding version
- Customer specific Blue Box

#### CCR 59 with oil

- Infeed conveyor
- Discharge conveyor with discharge cone
- Frequency inverter for variable cone speed
- Oil on discharge conveyor divider
- Oil on discharge conveyor rounder
- Signalisation oiling
- Customer specific Blue Box

#### WP BAKERY GROUP USA

1 Enterprise Drive, Suite 408 // Shelton, CT 06484 // PH: 203-929-6530 // FX: 203-929-7089  
info@wpbakerygroupusa.com // www.wpbakerygroupusa.com



**CCR 59**  
Conical Rounder

