

think process!



Werner & Pfleiderer
Bakery Technologies




ROTOTHERM[®] Green

Baking with energy saving factor

WP BAKERYGROUP

ROTOTHERM® GREEN



TECHNICAL DATA

		Standard version		High version	
		REC 1020 Green	REC 1280 Green	REC 1020 H Green	REC 1280 H Green

Dimensions (W x D x H)	mm	1,550 x 1,620 x 2,560	1,740 x 1,880 x 2,560	1,550 x 1,620 x 2,700	1,740 x 1,880 x 2,700
Required minimum ceiling height	mm	3,000		3,140	

ROTOTHERM® Green oil/gas-heated

Connected load rating (oil/natural gas/liquid gas)	kW	68	82	74	90
Electrical connected load ratings (control/motors/fans – no heating)		3.1 kW/3.8 kVA		3.1 kW/3.8 kVA	

ROTOTHERM® Green electrically heated

Electrical connected load rating	kW/kVA	60	75	60	75
----------------------------------	--------	----	----	----	----

Rotating table diameter	mm	1,100	1,300	1,100	1,300
for baking trays (e.g.)	mm	600 x 800	600 x 1,000	600 x 800	600 x 1,000
for baking trolley diagonal	mm	1,100	1,300	1,100	1,300
Max. baking area with 21 decks (see tray dimensions)	m²	10.1	12.6	-	-
Max. baking area with 23 decks (see tray dimensions)	m²	-	-	11	13.8
Max. rotating table load	kg	350	450	350	450
Max. baking trolley height	mm	1,810		1,950	
Oven weight	kg	2,000	2,400	2,100	2,500
Optional: Rotating table reinforcement, max. rotating table centric load	kg	450	550	450	550

WP BAKERY GROUP USA

2 Trap Falls Road, Suite 105, Shelton, CT 06484 // Phone 203-929-6530 // Fax 203-929-7089
info@wpbakerygroupusa.com // www.wpbakerygroupusa.com